



# PST KP738

## HIGH POWER PHASE CONTROL THYRISTOR FOR PHASE CONTROL APPLICATIONS

### Features :

- Blocking Capability up to 2200 V
- High dV/dt Capability
- All Diffused Structure
- Amplifying Gate Configuration
- Rugged Ceramic Hermetic Package

### ELECTRICAL CHARACTERISTICS AND RATINGS

#### Blocking

Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Repetitive peak reverse voltage	$V_{RRM}$		2200		V	$T_j = -40 \text{ }^{\circ}\text{C} \text{ to } 125 \text{ }^{\circ}\text{C}$
Repetitive peak off-state voltage	$V_{DRM}$		2200		V	$T_j = -40 \text{ }^{\circ}\text{C} \text{ to } 125 \text{ }^{\circ}\text{C}$
Non repetitive peak reverse voltage	$V_{RSM}$		2300		V	$T_j = -40 \text{ }^{\circ}\text{C} \text{ to } 125 \text{ }^{\circ}\text{C}$
Repetitive peak reverse current	$I_{RRM}$		200		mA	$T_j = T_{jmax}, V = V_{RRM}$
Repetitive peak off-state current	$I_{DRM}$		200		mA	$T_j = T_{jmax}, V = V_{DRM}$

#### Conducting

Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Average value of on-state current	$I_{T(AV)}$		3080		A	50 Hz sine wave, 180° conduction, $T_c = 85 \text{ }^{\circ}\text{C}$
RMS value of on-state current	$I_{T(RMS)}$		4836		A	50 Hz sine wave, 180° conduction, $T_c = 85 \text{ }^{\circ}\text{C}$
Surge non repetitive current	$I_{TSM}$		57		kA	50 Hz sine wave Half cycle
$I^2 t$	$I^2 t$		16245		$\text{kA}^2\text{s}$	$V_R = 0$ $T_j = 125 \text{ }^{\circ}\text{C}$
Peak on-state voltage	$V_{TM}$		1.15		V	On-state current 2000 A, $T_j = T_{jmax}$
Threshold voltage	$V_{T(TO)}$		0.94		V	$T_j = T_{jmax}$
On-state slope resistance	$r_T$		0.104		$\text{m}\Omega$	$T_j = T_{jmax}$
Holding current	$I_H$			100	mA	$V_D = 24 \text{ V}; I_T = 2.5 \text{ A}$
Latching current	$I_L$			400	mA	$V_D = 24 \text{ V}; R_L = 12 \Omega$

# PST KP738

## HIGH POWER PHASE CONTROL THYRISTOR

### Triggering

Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Gate current	$I_{GT}$		300		mA	$V_D = 6 \text{ V}; R_L = 3 \Omega; T_j = -40 \text{ }^\circ\text{C}$
			200		mA	$V_D = 6 \text{ V}; R_L = 3 \Omega; T_j = 25 \text{ }^\circ\text{C}$
			125		mA	$V_D = 6 \text{ V}; R_L = 3 \Omega; T_j = 25 \text{ }^\circ\text{C}$
Gate voltage	$V_{GT}$		5		V	$V_D = 6 \text{ V}; R_L = 3 \Omega; T_j = -40 \text{ }^\circ\text{C}$
			3		V	$V_D = 6 \text{ V}; R_L = 3 \Omega; T_j = 0 \div 125 \text{ }^\circ\text{C}$
		0.3			V	$V_D = V_{DRM}; R_L = 10 \text{ k}\Omega; T_j = 125 \text{ }^\circ\text{C}$
Peak gate current	$I_{GM}$		10		A	
Peak reverse gate voltage	$V_{RGM}$		5		V	
Peak gate power dissipation	$P_{GM}$		200		W	
Average gate power dissipation	$P_{G(AV)}$		5		W	

### Switching




Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Critical rate of rise of on-state current	$di/dt$	200			A/ $\mu$ s	Switching from $V_{DRM} \leq 1000 \text{ V}$
Critical rate of rise of on-state voltage	$dv/dt$	500			V/ $\mu$ s	Linear ramp up to 80% of $V_{DRM}$
Gate controlled delay time	$t_d$		3	2.5	$\mu$ s	$I_{TM} = 50 \text{ A}; V_D = 1500 \text{ V}; V_G = 20 \text{ V}$ $R_G = 20 \Omega; t_r = 0.1 \mu\text{s}; t_p = 20 \mu\text{s}$
Turn-off time	$t_q$		400	250	$\mu$ s	$I_{TM} = 500 \text{ A}; di/dt = 25 \text{ A}/\mu\text{s}; V_R \geq 50 \text{ V}$ $dV/dt = 200 \text{ V}/\mu\text{s}$ linear to 80% $V_{DRM}$ $V_G = 0 \text{ V}; T_j = 125 \text{ }^\circ\text{C}$
Reverse recovery charge	$Q_{rr}$			2000	$\mu$ C	$I_T = 2000 \text{ A}$ $di/dt = 20 \text{ A}/\mu\text{s}$
Reverse recovery current	$I_{rr}$			250	A/ $\mu$ s	$V_R \geq 50 \text{ V}$ $T_j = T_{jmax}$

### Thermal and mechanical


Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Operating temperature	$T_j$	-40	125		$^\circ\text{C}$	
Storage temperature	$T_{stg}$	-40	125		$^\circ\text{C}$	
Thermal resistance junction to case	$R_{th(j-c)}$		0.008		$^\circ\text{C/W}$	Double side cooled , DC
Thermal resistance case to sink	$R_{th(c-s)}$		0.002		$^\circ\text{C/W}$	Double side cooled, mounting surfaces smooth, flat and greased
Mounting force	$F$	40	50		kN	
Weight	$W$			1600	g	

# PST KP738

## HIGH POWER PHASE CONTROL THYRISTOR



## OUTLINE AND DIMENSIONS



mm	A	B	C	E
	84	118	110	35+/-1

- All the characteristics given in this data sheet are guaranteed only with uniform clamping force, cleaned and lubricated heatsink surfaces with flatness < 0.03 mm and roughness < 2µm