



Technical Data

PST MFC310

THYRISTOR / DIODE MODULE

Features:

- Electrically isolated base plate
- High surge capability
- Hard soldered joints for high reliability

Typical applications:

- DC motor control (e.g. for machine tools)
- Temperature control (e.g. for ovens, chemical processes)
- Professional light dimming (e.g. for studios, theaters)

ELECTRICAL CHARACTERISTICS AND RATINGS

Reverse blocking - Off-state

Device Type	V_{RRM} (1)	V_{DRM} (1)	V_{RSM} (1)
PST MFC310	1600 V	1600 V	1700 V

V_{RRM} = Repetitive peak reverse voltage

V_{DRM} = Repetitive peak off-state voltage

V_{RSM} = Non repetitive peak reverse voltage (2)

Repetitive reverse and off-state peak leakage current	I_{RRM}, I_{DRM}	70 mA (3)
Critical rate of rise of off-state voltage	dv/dt	1000 V/ μ s (4)

Notes:

All ratings are specified for $T_j = 25^\circ\text{C}$ unless otherwise stated.

(1) All voltage ratings are specified for an applied 50Hz/60Hz sinusoidal waveform over the temperature range -40 to +140 °C.

(2) 10 ms max. pulse width

(3) Maximum value for $T_j = T_{jmax}$

(4) Min. value for linear and exponential wave shape to 67% rated V_{DRM} . Gate open. $T_j = T_{jmax}$

Conducting

Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Average on-state / forward current	I_{TAV}, I_{FAV}		320		A	50 Hz sine wave, 180° conduction, $T_c = 85^\circ\text{C}$
RMS on-state / forward current	I_{TRMS}, I_{FRMS}		502		A	50 Hz sine wave, 180° conduction, $T_c = 85^\circ\text{C}$
Surge non repetitive current	I_{TSM}, I_{FSM}		8		kA	50 Hz sine wave Half cycle $V_R = 0$ $T_j = T_{jmax}$
$I^2 t$	$I^2 t$		320		kA ² s	
Peak on-state / forward voltage	V_{TM}, V_{FM}		1.28		V	On-state current 600 A, $T_j = T_{jmax}$
Threshold voltage	$V_{T(TO)}$		0.79		V	$T_j = T_{jmax}$
On-state slope resistance	r_T		0.81		mΩ	$T_j = T_{jmax}$
Holding current	I_H			150	mA	$T_j = 25^\circ\text{C}$
Latching current	I_L			200	mA	$T_j = 25^\circ\text{C}$
Critical rate of rise of on-state current	di/dt		100		A/ μ s	$I_G = 5 I_{GT}$, $t_r = 1 \mu\text{s}$, $T_j = T_{jmax}$
RMS isolation voltage	V_{INS}		3000		V	AC 50 Hz, 60 s

PST MFC310




THYRISTOR / DIODE MODULE

Triggering

Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Gate current	I_{GT}		200		mA	$V_D = 6 \text{ V}; R_L = 6 \Omega; T_j = 25^\circ\text{C}$
Gate voltage	V_{GT}		3		V	$V_D = 6 \text{ V}; R_L = 6 \Omega; T_j = 25^\circ\text{C}$

Thermal and mechanical characteristics and ratings


Parameter	Symbol	Min	Max	Typ	Unit	Conditions
Operating temperature	T_j	-40	140		°C	
Storage temperature	T_{stg}	-40	125		°C	
Thermal resistance junction to case (per module)	$R_{th(j-c)}$		0.061	°C/W	SIN 180° conduction mounting surfaces smooth, flat and greased	
Thermal resistance case to sink (per module)	$R_{th(c-s)}$		0.020			
Mounting torque case-heatsink	T	3	5		N·m	
Mounting torque busbar-terminals	T	12	15		N·m	
Weight	W			320	g	



PST MFC310

THYRISTOR / DIODE MODULE

OUTLINE AND DIMENSIONS



(all dimensions in mm)